



CAROTTAGE ET FORAGE DIAMANTÉ

DIAMOND CORING AND DRILLING

TOURET SWIVEL

Touret de levage Hoisting Swivel



Le touret de levage DATC est utilisé pour relever le train de tige.

La manille est attachée au câble au moyen d'un anneau de sécurité. Son rôle est d'éviter la torsion du câble.

DATC hoisting swivel is used for lifting the drill string.

The shackle is normally attached to the wire rope via a safety hook. Its role is to prevent the wire from coiling.

N° ARTICLE DES TOURETS DE LEVAGE / PART NOS. OF HOISTING SWIVELS

Filetage / Thread Connexion		Charge Maximale kN / Max Load kN			
		25 kN	50 kN	150 kN	200 kN
Tige / Rod CR42	Female / Box Mâle / Pin	HS0250C42B HS0250C42P			
Tige / Rod CR50	Female / Box Mâle / Pin	HS0250C50B HS0250C50P	HS0500C50B HS0500C50P		
Tige / Rod CR60	Female / Box Mâle / Pin	HS0250C60B HS0250C60P	HS0500C60B HS0500C60P	HS1500C60B HS1500C60P	
Tige / Rod AW	Female / Box Mâle / Pin	HS02500AWB HS02500AWP			
Tige / Rod BW	Female / Box Mâle / Pin		HS05000BWB HS05000BWP		
Tige / Rod NW	Female / Box Mâle / Pin			HS15000NWB HS15000NWP	
Tige / Rod AWL	Female / Box Mâle / Pin	HS02500AQB HS02500AQP			
Tige / Rod BWL	Female / Box Mâle / Pin	HS02500BQB HS02500BQP	HS05000BQB HS05000BQP		
Tige / Rod HWL	Female / Box Mâle / Pin	HS02500HQB HS02500HQP	HS05000HQB HS05000HQP	HS15000HQB HS15000HQP	HS20000HQB HS20000HQP
Tige / Rod HMWL	Mâle / Pin	HS02500HMQP	HS05000HMQP	HS15000HMQP	HS20000HMQP
Tige / Rod NWL	Female / Box Mâle / Pin	HS02500NQB HS02500NQP	HS05000NQB HS05000NQP	HS15000NQB HS15000NQP	
Tige / Rod NMWL	Mâle / Pin	HS02500NMQP	HS05000NMQP	HS15000NMQP	
Tige / Rod PWL	Female / Box Mâle / Pin			HS15000PQB HS15000PQP	HS20000PQB HS20000PQP
Tige / Rod Geobor-S	Female / Box Mâle / Pin			HS1500GBSB HS1500GBSP	HS2000GBSB HS2000GBSP
Tubage métrique 101 mm Mâle / Metric Casing 101 mm Pin				HS1500101P	
Tubage métrique 116 mm Mâle / Metric Casing 116 mm Pin				HS1500116P	
Tubage métrique 131 mm Mâle / Metric Casing 131 mm Pin				HS1500131P	
Tubage métrique 146 mm Mâle / Metric Casing 146 mm Pin				HS1500146P	
Tubage métrique 46 mm Mâle / Metric Casing 46 mm Pin		HS0250046P			
Tubage métrique 56 mm Mâle / Metric Casing 56 mm Pin			HS0500056P		
Tubage métrique 66 mm Mâle / Metric Casing 66 mm Pin			HS0500066P		
Tubage métrique 76 mm Mâle / Metric Casing 76 mm Pin			HS0500076P		
Tubage métrique 86 mm Mâle / Metric Casing 86 mm Pin			HS0500086P		
Tubage BS/DCDMA AW Mâle / BS/DCDMA Casing AW Pin		HS0250CAWP			
Tubage BS/DCDMA BW Mâle / BS/DCDMA Casing BW Pin			HS0500CBWP		
Tubage BS/DCDMA HW Mâle / BS/DCDMA Casing HW Pin				HS1500CHWP	
Tubage BS/DCDMA NW Mâle / BS/DCDMA Casing NW Pin			HS0500CNWP		
Tubage BS/DCDMA PW Mâle / BS/DCDMA Casing PW Pin				HS1500CPWP	
Tubage BS/DCDMA SW Mâle / BS/DCDMA Casing SW Pin					HS2000CSWP
Tubage BS/DCDMA UW Mâle / BS/DCDMA Casing UW Pin					HS2000CUWP
Tubage BS/DCDMA ZW Mâle / BS/DCDMA Casing ZW Pin					HS2000CZWP
Tubage LS-114 Mâle / Casing LS-114 Pin				HS150L114P	
Tubage LS-140 Mâle / Casing LS-140 Pin				HS150L140P	
Tubage LS-168 Mâle / Casing LS-168 Pin					HS200L168P
Tubage LS-194 Mâle / Casing LS-194 Pin					HS200L194P
Tubage LS-220 Mâle / Casing LS-220 Pin					HS200L220P
Tubage LS-95 Mâle / Casing LS-95 Pin				HS150L095P	

